





ATLANTA

HP-Servo-Hochleistungsgetriebe mit einstellbarem Zahnspiel <2' HP-High-performance gear units with adjustable backlash <2'

Achsabstand / Centre distance $a_o = 50 \text{ mm}$

Bestell-Nr. / Bild /Fig.1	Order code Bild/Fig. 2	Übersetzung i Ratio i	D ^{G7}	k	r	x	y	f ₁	e	G		J _{red} 10 ⁻⁴ kg m ²
58 43 105	58 83 105	4,75										0,4830
58 43 107	58 83 107	6,75										0,4140
58 43 109	58 83 109	9,25										0,3490
58 43 115	58 83 115	14,50										0,2800
58 43 120	58 83 120	19,50	95	222	152	5	42	100	115	M8	7,0	0,1960
58 43 129	58 83 129	29,00										0,2694
58 43 139	58 83 139	39,00										0,2310
58 43 150	58 83 150	50,00										0,2140
58 43 205	58 83 205	4,75										0,4830
58 43 207	58 83 207	6,75										0,4140
58 43 209	58 83 209	9,25										0,3490
58 43 215	58 83 215	14,50	50	222	152	5	42	100	95	M6	7,0	0,2800
58 43 220	58 83 220	19,50										0,1960
58 43 229	58 83 229	29,00										0,2694
58 43 239	58 83 239	39,00										0,2310
58 43 250	58 83 250	50,00										0,2140
58 43 305	58 83 305	4,75										0,4830
58 43 307	58 83 307	6,75										0,4140
58 43 309	58 83 309	9,25										0,3490
58 43 315	58 83 315	14,50										0,2800
58 43 320	58 83 320	19,50	80	222	152	5	42	100	100	M6	7,0	0,2960
58 43 329	58 83 329	29,00										0,2694
58 43 339	58 83 339	39,00										0,2310
58 43 350	58 83 350	50,00										0,2140
58 43 405	58 83 405	4,75										0,4830
58 43 407	58 83 407	6,75										0,4140
58 43 409	58 83 409	9,25										0,3490
58 43 415	58 83 415	14,50	95	232	162	5	52	105	115	M8	7,0	0,2800
58 43 420	58 83 420	19,50										0,1960
58 43 429	58 83 429	29,00										0,2694
58 43 439	58 83 439	39,00										0,2310
58 43 450	58 83 450	50,00										0,2140
58 43 505	58 83 505	4,75										0,4830
58 43 507	58 83 507	6,75										0,4140
58 43 509	58 83 509	9,25										0,3490
58 43 515	58 83 515	14,50										0,2800
58 43 520	58 83 520	19,50	60	234	164	4	54	100	75	M5	7,0	0,1960
58 43 529	58 83 529	29,00										0,2694
58 43 539	58 83 539	39,00										0,2310
58 43 550	58 83 550	50,00										0,2140
58 43 805	58 83 805	4,75										0,4830
58 43 807	58 83 807	6,75										0,4140
58 43 809	58 83 809	9,25										0,3490
58 43 815	58 83 815	14,50										0,2800
58 43 820	58 83 820	19,50	95	238	168	5	58	115	130	M8	8,0	0,1960
58 43 829	58 83 829	29,00										0,2694
58 43 839	58 83 839	39,00										0,2310
58 43 850	58 83 850	50,00										0,2140
58 43 905	58 83 905	4,75										0,4830
58 43 907	58 83 907	6,75										0,4140
58 43 909	58 83 909	9,25										0,3490
58 43 915	58 83 915	14,50										0,2800
58 43 920	58 83 920	19,50	110	238	168	5	58	115	130	M8	8,0	0,1960
58 43 929	58 83 929	29,00										0,2694
58 43 939	58 83 939	39,00										0,2310
58 43 950	58 83 950	50,00										0,2140



andere Achsabstände und Übersetzungen auf Anfrage / other centre distances and ratios on request.